



WE CAN SAFELY GIVE YOUR BUSINESS A LIFT  
**VEHICLE MOUNTED  
PLATFORMS FROM KALMAR**



**Kalmar**

Kalmar is part of Cargotec Corporation

# NATIONWIDE SUPPORT WITH PLENTY OF REACH PROVIDING YOU WITH CHOICE, FLEXIBILITY AND VALUE

## FOCUS ON SERVICE

Our popular range of non-insulated and insulated platforms combine safety and versatility to provide solutions for a wide selection of applications. We can also supply various host vehicles according to individual need – from panel vans and pickups to four wheel drive specialist vehicles. And as you'd expect, our approved installers ensure professional mounting of the platform followed by thorough testing and inspection.

Naturally, the best products deserve the best service and that's where Kalmar excels. From the supply of world-class products through to extensive support covering finance, parts, service contracts and technical assistance, you won't find a better way to give your business an expert lift.

Our team of over 60 engineers are fully equipped with mobile workshops which include on board air and power supplies, ready to bring the highest level of service to you quickly.



[www.kalmar-platforms.co.uk](http://www.kalmar-platforms.co.uk)

# KALMAR'S 13m to 75m PLATFORM RANGE



## ALTEC AT130F 13 METRE AERIAL PLATFORM



### Model ALTEC AT130F

Working height	13.0m
Side working reach (max)	7.4m
Platform capacity	200Kg
Rotation (non continuous)	360°
Flyboom travel	110°
Min GVW	3.5t

## SOCAGE APACHE T15/T17/T20/T23 14 to 22 METRE AERIAL PLATFORM



### Model SOCAGE APACHE T15/T17/T20/T23

Working height	14.1m to 22.5m
Side working reach (max)	8.8m to 10.5m
Platform capacity	200Kg
Rotation (non continuous)	700° to continuous
Min GVW	3.5t

## SOCAGE APACHE A15/A14/A17/A20

12 to 20 METRE AERIAL PLATFORM



### Model SOCAGE APACHE A15/A14/A17/A20

Working height	12.0m to 20.0m
Side working reach (max)	10.0m to 18.0m
Platform capacity	200Kg
Rotation (non continuous)	400° to 700°
Min GVW	2.8t to 3.5t





## SOCAGE APACHE DA18/DA320/DA22

17 to 22 METRE AERIAL PLATFORM



### Model SOCAGE APACHE DA18/DA320/DA22

Working height	17.4m to 22.1m
Side working reach (max)	7.7m to 11.3m
Platform capacity	200Kg
Rotation (non continuous)	700°
Min GVW	3.5t

## SOCAGE CHEYENNE TJ27/TJ30

26 to 30 METRE AERIAL PLATFORM



### Model SOCAGE CHEYENNE TJ27/TJ30

Working height	26.5m to 29.8m
Side working reach (max)	20.0m to 23.5m
Platform capacity	200Kg
Rotation (non continuous)	700°
Min GVW	7.5t/12.0t



**SOCAGE CHEYENNE**  
**TJ35/TJ42/TJ50/TJ65/TJJ75**  
 35 to 75 METRE AERIAL PLATFORM

**SOCAGE NAVAHO DAJ17/DA22**  
 16 to 22 METRE AERIAL PLATFORM



**Model SOCAGE CHEYENNE TJ35/TJ42/TJ50/TJ65/TJJ75**

Working height	35.0m to 74.8m
Side working reach (max)	26.5m to 36.3m
Platform capacity	300Kg to 360Kg
Rotation (non continuous)	700° to continuous
Min GVW	18.0t/26.0t/32.0t/40.0t

**Model SOCAGE NAVAHO DAJ17/DA22**

Working height	16.5m/22.3m
Side working reach (max)	7.4m/11.5m
Platform capacity	200Kg
Rotation (non continuous)	360°/700°
Total weight	1900kg/2850Kg

## ✓ KALMAR'S INSULATED 12m to 20m PLATFORM RANGE

### ALTEC AT33GS2/AT35G/AT37

✓ **INSULATED** 12 to 14 METRE AERIAL  
PLATFORM



#### Model ALTEC AT33GS2/AT35G/AT37

Insulated rating	ANSI Cat C, 46kV
Working height	12.5m/14.0m
Side working reach (max)	8.5m to 9.0m
Platform capacity	160Kg
Rotation (non continuous)	370° non continuous
Min GVW	5.5t/7.5t



INSULATED AERIAL PLATFORMS 12m to 20m

[www.kalmar-platforms.co.uk](http://www.kalmar-platforms.co.uk)



### ALTEC TA41S/TA41D/TA41M

✓ **INSULATED** 14 METRE AERIAL PLATFORM  
"M" MODEL WITH MATERIAL HANDLING

### ALTEC ALTEC AT40M/AT40P

✓ **INSULATED** 14 METRE AERIAL PLATFORM  
WITH MATERIAL HANDLING



#### Model ALTEC TA41S/TA41D/TA41M

Insulated rating	ANSI Cat C, 46kV
Working height	14.0m
Side working reach (max)	9.8m
Platform capacity	160Kg – 200Kg
Lifting jib capacity (M) models	Up to 386Kg
Rotation (non continuous)	90°
Min GVW	7.0t

#### Model ALTEC AT40M/AT40P

Insulated rating	ANSI Cat C, 46kV
Working height	14.0m
Side working reach (max)	9.8m
Platform capacity	181Kg – 272Kg
Lifting jib capacity (M) models	Up to 364Kg
Rotation (non continuous)	180°
Min GVW	6.5t

## ALTEC TA50/TA55/TA60

✓ INSULATED 16 to 20 METRE AERIAL PLATFORM WITH MATERIALS HANDLING



### Model ALTEC TA50/TA55/TA60

Insulated rating	ANSI Cat C, 46kV
Working height	16m to 20m
Side working reach (max)	11.5m to 12.7m
Platform capacity	272Kg
Lifting jib capacity (M) models	Up to 364Kg
Rotation (non continuous)	180°
Min GVW	12.0t



# ✓ KALMAR'S DRIVEN DEVICES 10m to 13m PLATFORM RANGE



## ✓ ALTEC AT37GW INSULATED 10 METRE AERIAL PLATFORM

## ✓ ALTEC DB35 DIGGER DERRICK INSULATED DIGGER, CRANE AND AERIAL PLATFORM



### Model ALTEC AT37GW

Insulated rating	ANSI Cat C, 46kV
Working height	10.4m
Side working reach (max)	9.1m
Platform capacity	136Kg
Rotation (non continuous)	180°
Min width	865mm

### Model ALTEC DB35 DIGGER DERRICK

Insulated rating	ANSI Cat C, 46kV
Sheave Height (max with jib)	13.1m
Side reach (pole handling)	9.2m
Dig radius (max)	6.9m
Platform capacity	136Kg
Lifting capacity (max)	1,361Kg
Rotation (non continuous)	180°
Min width	865mm
Weight	2,960Kg

**Kalmar Limited**

Siskin Drive, Coventry, CV3 4FJ, UK

tel: +44 (0) 24 7683 4500, fax: +44 (0) 24 7683 4523

email: [ukinfo@kalmarind.co.uk](mailto:ukinfo@kalmarind.co.uk)

**[www.kalmar-platforms.co.uk](http://www.kalmar-platforms.co.uk)**

**[www.kalmarind.co.uk](http://www.kalmarind.co.uk)**



Kalmar is part of Cargotec Corporation